

Exam4Test 350-001 Exams

Cisco CCIE Cisco Certified Internetworking Expert



Practice Exam: 350-001

Exam Number/Code: 350-001

Exam Name: CCIE Cisco Certified Internetworking Expert

Questions and Answers: 136 Q&As

Exam Description

Order : [350-001 Exam](#)

1. Exam4Test offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 350-001 Exam.

Exam4Test **Practice Exams** for 350-001 are written to the highest standards of technical accuracy, provided by our certified subject matter experts and published authors for development.

3. 100% Guarantee to Pass Your **CCIE** exam and get your **CCIE Certification**.

We guarantee your success in the first attempt. If you do not pass the **CCIE** "350-001" (CCIE Cisco Certified Internetworking Expert on your first attempt, send us the official result. We will give you a FULLY REFUND of your purchasing fee and send you another same value product for free.

4. Exam4Test CCIE 350-001 Exam Downloadable.

Our PDF or Testing Engine Preparation Material of CCIE 350-001 exam provides everything which you need to pass your exam. The CCIE Certification details are researched and produced by our Professional Certification Experts who are constantly using industry experience to produce precise, and logical. You may get "350-001 exam" questions from different websites or books, but logic is the key. Our Product will help you not only pass in the first CCIE Cisco Certified Internetworking Expert(CCIE) exam try, but also save your valuable time.

Comprehensive questions with complete details about 350-001 exam.

350-001 exam questions accompanied by exhibits. Verified Answers Researched by Industry Experts and almost 100% correct.

Drag and Drop questions as experienced in the Real CCIE exam. 350-001 exam questions updated on regular basis. Like actual CCIE Certification exams, 350-001 exam preparation is in multiple-choice questions (MCQs). Tested by many real CCIE exams before publishing.

Try free CCIE exam demo before you decide to buy it in <http://www.Exam4Test.com>

High quality and Valued for the 350-001 Exam: 100% Guarantee to Pass Your 350-001 exam and get your CCIE Certification. Come to <http://www.Exam4Test.com> The easiest and quickest way to get your CCIE Certification.

Exam4Test professional provides CCIE 350-001 the newest Q&A, completely covers 350-001 test original topic. With our completed CCIE resources, you will minimize your CCIE cost and be ready to pass your 350-001 test on Your First Try, 100% Money Back Guarantee included!

350-001 Exam Study Guide

350-001 exam is regarded as one of the most favourite [CCIE Certifications](#). Many IT professionals prefer to add 350-001 exam among their credentials. Exam4Test not only caters you all the information regarding the 350-001 exam but also provides you the excellent 350-001 study guide which makes the certification exam easy for you.

Exam4Test Engine Features

Comprehensive questions and answers about 350-001 exam

350-001 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

350-001 exam questions updated on regular basis

Same type as the certification exams, 350-001 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 350-001 exam demo before you decide to buy it in Exam4Test.com

Exam4Test Help You Pass Any IT Exam

[Exam4Test.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Cisco 350-001

Title : CCIE-Routing and Switching Written exam(4.1)

1. Which statement correctly describes the disabling of IP TTL propagation in an MPLS network?

- A. The TTL field from the IP packet is copied into the TTL field of the MPLS label header at the ingress edge LSR.
- B. TTL propagation cannot be disabled in an MPLS domain.
- C. TTL propagation is only disabled on the ingress edge LSR.
- D. The TTL field of the MPLS label header is set to 255.
- E. The TTL field of the IP packet is set to 0.

Answer: D

2. Loop guard and UniDirectional Link Detection both protect against Layer 2 STP loops. In which two ways does loop guard differ from UDLD in loop detection and prevention? (Choose two.)

- A. Loop guard can be used with root guard simultaneously on the same port on the same VLAN while UDLD cannot.
- B. UDLD protects against STP failures caused by cabling problems that create one-way links.
- C. Loop guard detects and protects against duplicate packets being received and transmitted on different ports.
- D. UDLD protects against unidirectional cabling problems on copper and fiber media.
- E. Loop guard protects against STP failures caused by problems that result in the loss of BPDUs from a designated switch port.

Answer: BE

3. Refer to the exhibit. In this network, R1 is configured not to perform autosummarization within EIGRP. What routes will R3 learn from R2 through EIGRP?

615795811.gif

- A. 172.30.1.0/24 and 10.1.2.0/24; EIGRP only performs autosummarization at the edge between two major networks.
- B. 172.30.0.0/16 and 10.1.2.0/24; R2 will perform autosummarization, although R1 will not.
- C. Since R2 is configured without autosummarization, it will not propagate the 172.30.1.0/24 route.
- D. 172.30.0.0/8 and 10.0.0.0/8.

Answer: A

4. If a port configured with STP loop guard stops receiving BPDUs, the port will be put into which state?

- A. learning state
- B. listening state
- C. forwarding state
- D. root-inconsistent state

Answer: D

5. Refer to the exhibit. Catalyst R is the root bridge for both VLAN 1 and VLAN 2. What is the easiest way to load-share traffic across both trunks and maintain redundancy in case a link fails, without using any type of EtherChannel link-bundling?

1069961955.gif

- A. Increase the root bridge priority (increasing the numerical priority number) for VLAN 2 on Catalyst D so that port D1 becomes the root port on Catalyst D for VLAN 2.
- B. Decrease the port priority on R2 for VLAN 2 on Catalyst R so that port D1 will be blocked for VLAN 2 and port D2 will remain blocked for VLAN 1.
- C. Decrease the path cost on R2 on Catalyst R for VLAN 2 so that port D1 will be blocked for VLAN 2 and port D2 will remain blocked for VLAN 1.
- D. Increase the root bridge priority (decreasing the numerical priority number) for VLAN 2 on Catalyst R so that R2 becomes the root port on Catalyst D for VLAN 2.

Answer: B

6. Which three port states are used by RSTP 802.1w? (Choose three.)

- A. Listening
- B. Learning
- C. Forwarding
- D. Blocking
- E. Discarding
- F. Disabled

Answer: BCE

7. Refer to the exhibit. Voice traffic is marked "precedence 5." How much bandwidth is allocated for voice traffic during periods of congestion?

- A. a minimum of 48 kb/s
- B. a maximum of 48 kb/s
- C. a minimum of 48% of the available bandwidth
- D. a maximum of 48% of the available bandwidth

Answer: B

8. When STP UplinkFast is enabled on a switch utilizing the default bridge priority, what will the new bridge priority be changed to?

- A. 8192
- B. 16384
- C. 49152
- D. 65535

Answer: C

9. Refer to the exhibit. In the diagram, the switches are running IEEE 802.1w RSPT. On which ports should root guard be enabled in order to facilitate deterministic root bridge election under normal and failure scenarios?

1331379426.gif

- A. GE-3/1, GE-3/2
- B. FE-2/1, FE-3/2
- C. GE-1/1, GE-1/2
- D. GE-4/1, GE-4/2

E. GE-2/1, GE-2/2

F. GE-3/1, GE-3/2, GE-4/1, GE-4/2, FE-2/1, FE-3/2

Answer: F

10. Which of these is mandatory when configuring Cisco IOS Firewall?

- A. Cisco IOS IPS enabled on the untrusted interface
- B. NBAR enabled to perform protocol discovery and deep packet inspection
- C. a route map to define the trusted outgoing traffic
- D. a route map to define the application inspection rules
- E. an inbound extended ACL applied to the untrusted interface

Answer: E

11. Refer to the exhibit. Which of these is applied to the Bearer class?

- A. WRED
- B. traffic shaping
- C. packet marking
- D. packet classification
- E. FIFO queuing within the class

Answer: E

12. Two routers configured to run BGP have been connected to a firewall, one on the inside interface and one on the outside interface. BGP has been configured so the two routers should peer, including the correct BGP session endpoint addresses and the correct BGP session hop-count limit (EBGP multihop). What is a good first test to see if BGP will work across the firewall?

- A. Attempt to TELNET from the router connected to the inside of the firewall to the router connected to the outside of the firewall. If telnet works, BGP will work, since telnet and BGP both use TCP to transport data.
- B. Ping from the router connected to the inside interface of the firewall to the router connected to the outside interface of the firewall. If you can ping between them, BGP should work, since BGP uses IP to transport packets.
- C. There is no way to make BGP work across a firewall without special configuration, so there is no simple test that will show you if BGP will work or not, other than trying to start the peering session.
- D. There is no way to make BGP work across a firewall.

Answer: A

13. Which of these best describes the actions taken when a VTP message is received on a switch configured with VTP mode "transparent"?

- A. VTP updates are ignored and forwarded out all ports.
- B. VTP updates are ignored and forwarded out trunks only.
- C. VTP updates are made to the VLAN database and are forwarded out trunks only.
- D. VTP updates are ignored and are not forwarded.

Answer: B

14. Spanning Tree Protocol IEEE 802.1s defines the ability to deploy which of these?

- A. one global STP instance for all VLANs
- B. one STP instance for each VLAN
- C. one STP instance per set of VLANs
- D. one STP instance per set of bridges

Answer: C

15. Which two of these are used in the selection of a root bridge in a network utilizing Spanning Tree Protocol IEEE 802.1D? (Choose two.)

- A. Designated Root Cost
- B. bridge ID priority
- C. max age
- D. bridge ID MAC address

E. Designated Root Priority

F. forward delay

Answer: BD

16. Refer to the exhibit. In the diagram, the switches are running IEEE 802.1s MST. Which ports are in the MST blocking state?

1042725475.gif

A. GE-1/2 and GE 2/1

B. GE-1/1 and GE-2/2

C. GE-3/2 and GE 4/1

D. no ports are in the blocking state

E. There is not enough information to determine which ports are in the blocking state.

Answer: D

17. The classic Spanning Tree Protocol (802.1D 1998) uses which sequence of variables to determine the best received BPDU?

A. 1) lowest root bridge id, 2) lowest sender bridge id, 3) lowest port id, 4) lowest root path cost

B. 1) lowest root path cost, 2) lowest root bridge id, 3) lowest sender bridge id, 4) lowest sender port id

C. 1) lowest root bridge id, 2) lowest sender bridge id, 3) lowest root path cost 4) lowest sender port id

D. 1) lowest root bridge id, 2) lowest root path cost, 3) lowest sender bridge id, 4) lowest sender port id

Answer: D

18. What is the purpose of an explicit "deny any" statement at the end of an ACL?

A. none, since it is implicit

B. to enable Cisco IOS IPS to work properly; however, it is the deny all traffic entry that is actually required

C. to enable Cisco IOS Firewall to work properly; however, it is the deny all traffic entry that is actually required

D. to allow the log option to be used to log any matches

E. to prevent sync flood attacks

F. to prevent half-opened TCP connections

Answer: D

19. What is the purpose of the STP PortFast BPDU guard feature?

A. enforce the placement of the root bridge in the network

B. ensure that a port is transitioned to a forwarding state quickly if a BPDU is received

C. enforce the borders of an STP domain

D. ensure that any BPDUs received are forwarded into the STP domain

Answer: C

20. Refer to the exhibit. In this network, R1 has been configured to advertise a summary route, 192.168.0.0/22, to R2. R2 has been configured to advertise a summary route, 192.168.0.0/21, to R1. Both routers have been configured to remove the discard route (the route to null created when a summary route is configured) by setting the administrative distance of the discard route to 255.

What will happen if R1 receives a packet destined to 192.168.3.1?

562351331.gif

A. The packet will loop between R1 and R2.

B. It is not possible to set the administrative distance on a summary to 255.

C. The packet will be forwarded to R2, where it will be routed to null0.

D. The packet will be dropped by R1, since there is no route to 192.168.3.1.

Answer: A

[More 350-001 Information](#)

Related 350-001 Exams

350-001 CCIE Cisco Certified Internetworking Expert

350-018 CCIE Pre-Qualification Test for Security

350-001-LAB CCIE-ROUTING AND SWITCHING QUALIFICATION (Lab exam)

350-029 CCIE SP Written Exam

351-001 CCIE Routing and Switching Written 3.0 Beta

350-030 CCIE Voice Written

350-018-LAB CCIE Pre-Qualification Test for Security (Lab exam)

350-040 CCIE Storage Networking

350-050 CCIE Wireless Beta Written Exam

350-020 CCIE SP Optical Qualification Exam

350-022 CCIE Written, Service Provider: DSL

350-027 CCIE Written: Metro Ethernet

350-025 CCIE Service Provider Dial

350-024 CCIE SP IP Telephony Qualification Exam

350-021 CCIE SP Cable Qualification Exam

351-018 Security 3.0 Beta

350-023 CCIE Written: WAN Switching

350-026 CCIE SP Content Networking ENU

350-001GB2312-LAB CCIE-Routing and Switching Written exam

Other Cisco Exams

<u>642-105</u>	<u>650-178</u>	<u>350-001-</u>	<u>650-059</u>	<u>642-902</u>	<u>642-531</u>	<u>642-342</u>	<u>640-801</u>
		<u>LAB</u>	<u>642-444</u>	<u>646-985</u>	<u>642-831</u>	<u>642-091</u>	<u>642-631</u>
<u>642-359</u>	<u>642-983</u>	<u>350-030</u>	<u>642-978</u>	<u>642-372</u>	<u>642-241</u>	<u>642-513</u>	