


Exam4Test 640-822 Exams

Cisco Interconnecting Cisco Networking Devices Part 1



Practice Exam: 640-822

Exam Number/Code: 640-822

Exam Name: *Interconnecting Cisco Networking Devices Part 1*

Questions and Answers: 95 Q&As

Exam Description

Order : [640-822 Exam](#)

1. Exam4Test offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 640-822 Exam.

Exam4Test **Practice Exams** for 640-822 are written to the highest standards of technical accuracy, provided by our certified subject matter experts and published authors for development.

3. 100% Guarantee to Pass Your **CCNA** exam and get your *CCNA Certification*.

We guarantee your success in the first attempt. If you do not pass the **CCNA** "640-822" (Interconnecting Cisco Networking Devices Part 1) on your first attempt, send us the official result. We will give you a FULLY REFUND of your purchasing fee and send you another same value product for free.

4. Exam4Test CCNA 640-822 Exam Downloadable.

Our PDF or Testing Engine Preparation Material of CCNA 640-822 exam provides everything which you need to pass your exam. The CCNA Certification details are researched and produced by our Professional Certification Experts who are constantly using industry experience to produce precise, and logical. You may get "640-822 exam" questions from different websites or books, but logic is the key. Our Product will help you not only pass in the first Interconnecting Cisco Networking Devices Part 1(CCNA) exam try, but also save your valuable time.

Comprehensive questions with complete details about 640-822 exam.

640-822 exam questions accompanied by exhibits. Verified Answers Researched by Industry Experts and almost 100% correct.

Drag and Drop questions as experienced in the Real CCNA exam. 640-822 exam questions updated on regular basis

Like actual CCNA Certification exams, 640-822 exam preparation is in multiple-choice questions (MCQs). Tested by many real CCNA exams before publishing.

Try free CCNA exam demo before you decide to buy it in <http://www.Exam4Test.com>

High quality and Valued for the 640-822 Exam: 100% Guarantee to Pass Your 640-822 exam and get your CCNA Certification. Come to <http://www.Exam4Test.com> The easiest and quickest way to get your CCNA Certification.

Exam4Test professional provides CCNA 640-822 the newest Q&A, completely covers 640-822 test original topic. With our completed CCNA resources, you will minimize your CCNA cost and be ready to pass your 640-822 test on Your First Try, 100% Money Back Guarantee included!

640-822 Exam Study Guide

640-822 exam is regarded as one of the most favourite [CCNA Certifications](#). Many IT professionals prefer to add 640-822 exam among their credentials. Exam4Test not only caters you all the information regarding the 640-822 exam but also provides you the excellent 640-822 study guide which makes the certification exam easy for you.

Exam4Test Engine Features

Comprehensive questions and answers about 640-822 exam

640-822 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

640-822 exam questions updated on regular basis

Same type as the certification exams, 640-822 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 640-822 exam demo before you decide to buy it in Exam4Test.com

Exam4Test Help You Pass Any IT Exam

[Exam4Test.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Cisco 640-822

Title : Interconnecting Cisco Networking Devices Part 1

1. Refer to the exhibit. The ports that are shown are the only active ports on the switch. The MAC address table is shown in its entirety. The Ethernet frame that is shown arrives at the switch.

What two operations will the switch perform when it receives this frame? (Choose two.)

- A. The MAC address of 0000.00aa.aaaa will be added to the MAC address table.
- B. The MAC address of 0000.00dd.dddd will be added to the MAC address table.
- C. The frame will be forwarded out port fa0/3 only.
- D. The frame will be forwarded out fa0/1, fa0/2, and fa0/3.
- E. The frame will be forwarded out all the active ports.

Answer: AD

2. Refer to the exhibit. What could be possible causes for the "Serial0/0 is down" interface status? (Choose two.)

- A. A Layer 1 problem exists.
- B. The bandwidth is set too low.
- C. A protocol mismatch exists.
- D. An incorrect cable is being used.
- E. There is an incorrect IP address on the Serial 0/0 interface.

Answer: AD

3. Which line from the output of the show ip interface command indicates that there is a Layer 1 problem?

- A. Serial0/1 is up, line protocol is up
- B. Serial0/1 is up, line protocol is down
- C. Serial0/1 is down, line protocol is down
- D. Serial0/1 is administratively down, line protocol is down

Answer: C

4. Refer to the exhibit. A network technician is attempting to use HyperTerminal to configure a new router using the settings shown. What is the reason the technician is unable to connect to the router?

- A. The bits per second should be set to 9600.
- B. The data bits should be set to 6.
- C. Parity should be set to mark.
- D. The stop bits should be set to 2.
- E. Flow control should be set to hardware.

Answer: A

5. What are two advantages of Layer 2 Ethernet switches over hubs? (Choose two.)

- A. decreasing the number of collision domains
- B. filtering frames based on MAC addresses
- C. allowing simultaneous frame transmissions
- D. increasing the size of broadcast domains
- E. increasing the maximum length of UTP cabling between devices

Answer: BC

6. Refer to the exhibit. A network device needs to be installed in the place of the icon labeled Network Device to accommodate a leased line attachment to the Internet. Which network device and interface configuration meets the minimum requirements for this installation?

- A. a router with two Ethernet interfaces
- B. a switch with two Ethernet interfaces
- C. a router with one Ethernet and one serial interface
- D. a switch with one Ethernet and one serial interface
- E. a router with one Ethernet and one modem interface

Answer: C

7. Refer to the exhibit. Two buildings on the San Jose campus of a small company must be connected to use Ethernet with a bandwidth of at least 100 Mbps. The company is concerned about possible problems from voltage potential differences between the two buildings. Which media type should be used for the connection?

- A. UTP cable
- B. STP cable
- C. coaxial cable
- D. fiber optic cable

Answer: D

8. Refer to the exhibit. A network technician has added host A to the network. Host A cannot communicate on the network. A ping that is issued on the host to address 127.0.0.1 fails. What is the problem?

- A. The router is not forwarding the ping packets to network 127.0.0.0.
- B. The remote host at 127.0.0.1 is unreachable.
- C. The default gateway is incorrect.
- D. The IP address of host A is incorrect.
- E. The TCP/IP protocols are not loaded.

Answer: E

9. Refer to the exhibits labeled A through E. All devices are to be connected over Ethernet. Which three device-to-device configurations are likely to require the use of a crossover connection? (Choose three.)

- A. exhibit A
- B. exhibit B
- C. exhibit C
- D. exhibit D
- E. exhibit E

Answer: ADE

10. Refer to the exhibit. Workstation A must be able to telnet to switch SW-A through router RTA for management purposes. What must be configured for this connection to be successful?

- A. VLAN 1 on RTA
- B. default gateway on SW-A
- C. IP routing on SW-A
- D. cross-over cable connecting SW-A and RTA

Answer: B

11. Refer to the exhibit. A network has been planned as shown. Which three statements accurately describe the areas and devices in the network plan? (Choose three.)

- A. Network Device A is a switch.
- B. Network Device B is a switch.
- C. Network Device A is a hub.
- D. Network Device B is a hub.
- E. Area 1 contains a Layer 2 device.
- F. Area 2 contains a Layer 2 device.

Answer: ADE

12. An Ethernet cable is attached to a PC NIC and then attached to a switch port. The PC power is turned on and the switch port link LED turns green. The link light indicates what two conditions? (Choose two.)

- A. Layer 2 communication has been established between the PC and switch.
- B. The PC has received a DHCP address.
- C. Traffic is being sent from the switch to the PC.
- D. If flashing, the green LED indicates port speed of 100 Mb/s.
- E. The Layer 1 media is functioning between the PC and switch.
- F. The switch port is functioning as a half-duplex connection.

Answer: AE

13. Refer to the exhibit. The wire scheme that is shown is terminated at each end with an RJ-45 connector. What cable type does the wire diagram represent?

- A. an Ethernet straight-through cable
- B. a serial crossover cable
- C. a serial straight-through cable
- D. an Ethernet crossover cable
- E. a rollover cable

Answer: D

14. Refer to the exhibit. A network administrator has configured a Catalyst 2950 switch for remote management by pasting into the console the configuration commands that are shown in the exhibit. However, a Telnet session cannot be successfully established from a remote host. What should be done to fix this problem?

- A. Change the first line to interface fastethernet 0/1.
- B. Change the first line to interface vlan 0/1.
- C. Change the fifth line to ip default-gateway 192.168.17.241.
- D. Change the fifth line to ip route 0.0.0.0 0.0.0.0 192.168.17.1.
- E. Change the sixth line to line con 0.

Answer: C

15. Refer to the exhibit. Pierre has just installed the mail server and Switch2. For security reasons UDP packets are not permitted outbound on the Fa0/1 router interface. Pierre is now at his workstation testing the new installation and is not able to establish SMTP communication to the mail server.

What is the most likely cause for lack of communication between Pierre's workstation and the mail server?

- A. The crossover cable should be a straight-through cable.
- B. UDP is blocked coming out of the Fa0/1 interface on the router.
- C. The server should be directly connected to the router.

D. The IP addresses are all on the same network. No router is required.

Answer: A

[More 640-822 Information](#)

Related 640-822 Exams

[640-802](#) *Cisco Certified Network Associate*

[640-822](#) *Interconnecting Cisco Networking Devices Part 1*

[640-816](#) *Interconnecting Cisco Networking Devices Part 2*

[640-801](#) *Cisco Certified Network Associate (CCNA)*

[640-553](#) *IINS Implementing Cisco IOS Network Security*

[640-721](#) *Implementing Cisco Unified Wireless Networking Essentials (IUWNE)*

[640-811](#) *Interconnecting Cisco Networking Devices*

[640-821](#) *Introduction to Cisco Networking Technologies*

Other Cisco Exams

[646-392](#)

[642-274](#)

[642-105](#)

[646-003](#)

[650-251](#)

[640-816](#)

[642-661](#)

[646-562](#)

[642-873](#)

[642-821](#)

[642-832](#)

[642-071](#)

[642-582](#)

[646-362](#)

[646-653](#)

[646-391](#)

[642-355](#)

[642-415](#)

[642-381](#)

[642-651](#)