

Exam4Test 642-691 Exams

Cisco CCIP BGP + MPLS Exam (BGP + MPLS)



Practice Exam: 642-691

Exam Number/Code: 642-691

Exam Name: CCIP BGP + MPLS Exam (BGP + MPLS)

Questions and Answers: 80 Q&As

Exam Description

Order : [642-691 Exam](#)

1. Exam4Test offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 642-691 Exam.

Exam4Test **Practice Exams** for 642-691 are written to the highest standards of technical accuracy, provided by our certified subject matter experts and published authors for development.

3. 100% Guarantee to Pass Your **CCIP** exam and get your **CCIP Certification**.

We guarantee your success in the first attempt. If you do not pass the **CCIP** "642-691" (CCIP BGP + MPLS Exam (BGP + MPLS)) on your first attempt, send us the official result. We will give you a FULLY REFUND of your purchasing fee and send you another same value product for free.

4. Exam4Test CCIP 642-691 Exam Downloadable.

Our PDF or Testing Engine Preparation Material of CCIP 642-691 exam provides everything which you need to pass your exam. The CCIP Certification details are researched and produced by our Professional Certification Experts who are constantly using industry experience to produce precise, and logical. You may get "642-691 exam" questions from different websites or books, but logic is the key. Our Product will help you not only pass in the first CCIP BGP + MPLS Exam (BGP + MPLS)(CCIP) exam try, but also save your valuable time.

Comprehensive questions with complete details about 642-691 exam.

642-691 exam questions accompanied by exhibits. Verified Answers Researched by Industry Experts and almost 100% correct.

Drag and Drop questions as experienced in the Real CCIP exam. 642-691 exam questions updated on regular basis. Like actual CCIP Certification exams, 642-691 exam preparation is in multiple-choice questions (MCQs). Tested by many real CCIP exams before publishing.

Try free CCIP exam demo before you decide to buy it in <http://www.Exam4Test.com>

High quality and Valued for the 642-691 Exam: 100% Guarantee to Pass Your 642-691 exam and get your CCIP Certification. Come to <http://www.Exam4Test.com> The easiest and quickest way to get your CCIP Certification.

Exam4Test professional provides CCIP 642-691 the newest Q&A, completely covers 642-691 test original topic. With our completed CCIP resources, you will minimize your CCIP cost and be ready to pass your 642-691 test on Your First Try, 100% Money Back Guarantee included!

642-691 Exam Study Guide

642-691 exam is regarded as one of the most favourite [CCIP Certifications](#). Many IT professionals prefer to add 642-691 exam among their credentials. Exam4Test not only caters you all the information regarding the 642-691 exam but also provides you the excellent 642-691 study guide which makes the certification exam easy for you.

Exam4Test Engine Features

Comprehensive questions and answers about 642-691 exam

642-691 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

642-691 exam questions updated on regular basis

Same type as the certification exams, 642-691 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 642-691 exam demo before you decide to buy it in Exam4Test.com

Exam4Test Help You Pass Any IT Exam

[Exam4Test.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Cisco 642-691

Title : Cisco CCIP BGP + MPLS Exam (BGP + MPLS)

1. In a central services topology, which routes do client VRFs contain?

- A. routes from the client site, but not from the server site
- B. routes from the server site, but not from the client site
- C. routes from both the client site and the server site
- D. only EBGP routes from either the client site or the server site

Answer: C

2. As the penalty for a flapping route decreases and falls below a certain limit, the route is unsuppressed. What is the name of that limit?

- A. half-life limit
- B. suppress limit
- C. max-suppress-time limit
- D. reuse limit
- E. unsuppress limit
- F. penalty limit

Answer: D

3. Which two statements about a transit AS are correct? (Choose two.)

- A. A transit AS has eBGP connection(s) to only one external AS.
- B. Routes between ASs are always exchanged via eBGP.
- C. A transit AS uses an IGP like OSPF or ISIS to propagate the external networks within the transit AS.
- D. Core routers within a transit AS normally use default routing to reach the external networks.
- E. iBGP sessions can be established between non directly connected routers.

Answer: BE

4. Which two of the following statements regarding LDP are true? (Choose two.)

- A. LDP can also be used between nonadjacent routers using multicast LDP hello messages.
- B. LDP does not require periodic hello messages once the LDP session has been established between the LDP peers.
- C. LDP hello messages use TCP packets with a destination port number of 646.
- D. Multiple sessions can be established between a pair of LSRs if they use multiple label spaces.
- E. Per-platform label space can be identified by a label space ID of 0 in the LDP identifier field.

Answer: DE

5. Based on the network diagram shown in the exhibit, both R5 and R6 are clients of the R2 RR. When the 10.0.0.0/8 iBGP update from R3 is received by the R2 RR, which router(s) will R2 reflect the update to?

- A. R1 only
- B. R5 and R6
- C. R5, R6 and R1
- D. R4, R5 and R6
- E. R4, R5, R6 and R1
- F. to no other router

Answer: C

6. On a dedicated subinterface implementation, PE-2 must establish an address-family vrf IPv4 BGP neighbor relationship with which router?

- A. CE-1
- B. CE-2
- C. PE-1
- D. PE-IG
- E. CE-1 and CE-2
- F. PE-1 and PE-IG

Answer: B

7. What are three drawbacks of a peer-to-peer VPN using a shared provider edge (PE) router? (Choose three.)

- A. A full mesh of virtual circuits is required between the customer sites.
- B. All the customers have to share a common IP address space.
- C. Optimal routing between customer sites cannot be guaranteed.
- D. The shared PE router has to know all routes for all customers.
- E. Packet filters are required on the PE routers.

Answer: BDE

8. Which command is used to configure the external, confederation-wide AS number?

- A. `router(config)#router bgp {as-number}`
- B. `router(config-router)#bgp confederation peers {as-number}`
- C. `router(config-router)#bgp confederation identifier {as-number}`
- D. `router(config-router)#bgp cluster-id {as-number}`
- E. `router(config-router)#neighbor {ip address} remote-as {as-number}`

Answer: C

9. Refer to the diagram. What problem can be caused by the second P router summarizing the loopback address of the egress PE router?

- A. The first P router will be faced with a VPN label which it does not understand.
- B. The second P router will be faced with a VPN label which it does not understand.
- C. The egress PE router will not be able to establish a label switch path (LSP) to the ingress PE router.
- D. A label switch path (LSP) will be established from the ingress PE router to the egress PE router, an event that is not desirable.
- E. The ingress PE router will not be able to receive the VPN label from the egress PE router via MP-IBGP.

Answer: B

10. Refer to the exhibit. Which two of the following statements about the MPLS configurations are true? (Choose two.)
- A. The VPI range being configured is the default VPI range.
 - B. The router is missing the mpls label protocol ldp configuration command on its ATM 0/0.1 subinterface to make it an LC-ATM enabled subinterface.
 - C. There is a problem with the configurations because the control VC should be set to 0 32 instead.
 - D. The ATM switch is using VC merge since VC merge is enabled by default.
 - E. For MPLS label allocations, both VPI 6 and 7 can be used.

Answer: DE

11. Based on the network diagram shown in the exhibit, what is the correct configuration on the customer edge route used to conditionally announce the customer networks to the ISP?

A. router bgp 65001

! neighbor commands not shown

network 192.168.8.0 mask 255.255.252.0

!

ip route 192.168.8.0 255.255.252.0 192.168.8.33

B. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0 summary-only

!

ip route 192.168.8.0 255.255.252.0 192.168.8.33

C. router bgp 65001

! neighbor commands not shown

network 192.168.8.0

network 192.168.9.0

network 192.168.10.0

network 192.168.11.0

!

ip route 192.168.8.0 255.255.255.0 null0

ip route 192.168.9.0 255.255.255.0 null0

ip route 192.168.10.0 255.255.255.0 null0

ip route 192.168.11.0 255.255.255.0 null0

D. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0 summary-only

!

router ospf 1

network 192.168.8.0 0.0.3.255 area 0

E. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0

!

ip route 192.168.8.0 255.255.252.0 null0

Answer: A

12. Based on the topology diagram shown in the exhibit, when should BGP be used as the routing protocol between the customer and the ISP?

A. If physical link failures can not be detected by the link-level procedures.

B. If the customer wants to affect how the ISP will route the customer's traffic out to the rest of the Internet.

C. If the ISP does not support static routing with the customer.

D. If the customer is using provider-assigned (PA) addresses inside the customer's network.

E. If the customer is using private addresses inside the customer's network.

Answer: A

13. Which show command can be used to display the originator ID and cluster-list?

- A. show ip bgp
- B. show ip bgp sum
- C. show ip route bgp
- D. show ip route {prefix}
- E. show ip bgp {prefix}
- F. show ip bgp neighbors {ip address}

Answer: E

14. For which purpose is the command mpls ldp maxhops used?

- A. In large ATM-MPLS networks, the LFIB can become too large and it may be necessary to limit the maximum diameter of the MPLS LSPs.
- B. Because downstream-on-demand label allocation uses hop count to control loop detection, it maybe necessary to limit the maximum diameter of the MPLS network.
- C. Because end-to-end delay can cause problems with some voice applications, it may be necessary to limit the maximum diameter of the MPLS network.
- D. When interconnecting large frame mode MPLS and cell mode networks it may be necessary to limit the maximum network diameter to prevent forwarding loops.

Answer: B

15. What does the following command accomplish? sanjose#clear ip bgp 10.1.1.1 in prefix-filter

- A. The sanjose router will perform an outbound soft reconfig to the 10.1.1.1 neighbor.
- B. The sanjose router will send out the ORF prefix-list so that a new route refresh will be received from the 10.1.1.1 neighbor.
- C. The 10.1.1.1 router will perform an inbound soft reconfig on the updates from the sanjose neighbor.
- D. The 10.1.1.1 router will send out the ORF prefix-list so that a new route refresh will be received from the sanjose neighbor.
- E. The bgp session between the sanjose and the 10.1.1.1 router will be reset so that all the new bgp updates from the 10.1.1.1 router can be processed by the inbound prefix-list at the sanjose router.
- F. The bgp session between the sanjose and the 10.1.1.1 router will be reset so that all the new bgp updates from the sanjose router can be processed by the inbound prefix-list at the 10.1.1.1 router.

Answer: B

[More 642-691 Information](#)

Related 642-691 Exams

[642-642](#) *Quality of Service (QoS)*

[642-691](#) *CCIP BGP + MPLS Exam (BGP + MPLS)*

[642-611](#) *CCIP Implementing Cisco MPLS Exam (MPLS)*

[642-661](#) *CCIP Configuring BGP on Cisco Routers (BGP)*

Other Cisco Exams

[650-178](#) [642-241](#) [642-067](#) [640-553](#) [650-575](#) [642-415](#) [642-871](#) [646-223](#)

[646-003](#) [642-544](#) [642-436](#) [642-054](#) [642-566](#) [642-372](#) [642-651](#) [642-523](#)

[642-901](#) [642-162](#) [642-832](#) [350-027](#)