


## **Exam4Test 642-811 Exams**

### *Cisco Building Cisco Multilayer Switched Networks (BCMSN)*



**Practice Exam:** 642-811

**Exam Number/Code:** 642-811

**Exam Name:** Building Cisco Multilayer Switched Networks (BCMSN)

**Questions and Answers:** 266 Q&As

#### **Exam Description**

Order : [642-811 Exam](#)

1. Exam4Test offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 642-811 Exam.

Exam4Test **Practice Exams** for 642-811 are written to the highest standards of technical accuracy, provided by our certified subject matter experts and published authors for development.

3. 100% Guarantee to Pass Your **CCNP** exam and get your **CCNP Certification**.

We guarantee your success in the first attempt. If you do not pass the **CCNP** "642-811" (Building Cisco Multilayer Switched Networks (BCMSN) on your first attempt, send us the official result. We will give you a FULLY REFUND of your purchasing fee and send you another same value product for free.

4. Exam4Test CCNP 642-811 Exam Downloadable.

Our PDF or Testing Engine Preparation Material of CCNP 642-811 exam provides everything which you need to pass your exam. The CCNP Certification details are researched and produced by our Professional Certification Experts who are constantly using industry experience to produce precise, and logical. You may get "642-811 exam" questions from different websites or books, but logic is the key. Our Product will help you not only pass in the first Building Cisco Multilayer Switched Networks (BCMSN)( CCNP ) exam try, but also save your valuable time.

Comprehensive questions with complete details about 642-811 exam.

642-811 exam questions accompanied by exhibits. Verified Answers Researched by Industry Experts and almost 100% correct.

Drag and Drop questions as experienced in the Real CCNP exam. 642-811 exam questions updated on regular basis

Like actual CCNP Certification exams, 642-811 exam preparation is in multiple-choice questions (MCQs). Tested by many real CCNP exams before publishing.

Try free CCNP exam demo before you decide to buy it in <http://www.Exam4Test.com>

High quality and Valued for the 642-811 Exam: 100% Guarantee to Pass Your 642-811 exam and get your CCNP Certification. Come to <http://www.Exam4Test.com> The easiest and quickest way to get your CCNP Certification.

Exam4Test professional provides CCNP 642-811 the newest Q&A, completely covers 642-811 test original topic. With our completed CCNP resources, you will minimize your CCNP cost and be ready to pass your 642-811 test on Your First Try, 100% Money Back Guarantee included!

## 642-811 Exam Study Guide

642-811 exam is regarded as one of the most favourite [CCNP Certifications](#). Many IT professionals prefer to add 642-811 exam among their credentials. Exam4Test not only caters you all the information regarding the 642-811 exam but also provides you the excellent 642-811 study guide which makes the certification exam easy for you.

### Exam4Test Engine Features

Comprehensive questions and answers about 642-811 exam

642-811 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

642-811 exam questions updated on regular basis

Same type as the certification exams, 642-811 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 642-811 exam demo before you decide to buy it in Exam4Test.com

### Exam4Test Help You Pass Any IT Exam

[Exam4Test.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Cisco 642-811

Title : Building Cisco Multilayer Switched Networks(BCMSN)

1. Refer to the exhibit. Which set of commands contains the minimum number of commands necessary on the Cat\_3550 switch for the host in VLAN 2 to be able to ping the host in VLAN 3?

- A. ip routing
- B. ip routingrouter eigrp 1network 10.0.0.0
- C. router eigrp 1network 10.0.0.0
- D. ip routingrouter eigrp 1redistribute connectednetwork 10.0.0.0network 200.1.1.0no auto-summary
- E. ip routingrouter eigrp 1redistribute connectednetwork 10.0.0.0no auto-summary

Answer: E

2. Which is a valid multicast MAC address?

- A. 00-00-00-FA-11-67
- B. 01-00-E0-56-AE-3C
- C. 00-01-E0-A8-B2-C1
- D. 01-00-5E-0A-08-CF
- E. FF-FF-FF-FF-FF-FF

Answer: D

3. LAB

The information of the question

VTP Domain name : cisco

VLAN Ids 20 31

IP Addresses 172.16.71.1/24 172.16.132.1/24

These are your specific tasks:

1. Configure the VTP information with the distribution layer switch as the VTP server
2. Configure the VTP information with the access layer switch as a VTP client

3. Configure VLANs on the distribution layer switch
4. Configure inter-VLAN routing on the distribution layer switch
5. Specific VLAN port assignments will be made as users are added to the access layer switches in the future.
6. All VLANs and VTP configurations are to be completed in the global configuration. To configure the switch click on the host icon that is connected to the switch by way of a serial console cable.

Correct Answers:

vtp server configuration:

```
switch#conf t
switch(config)#vtp mode server
switch(config)#vtp domain CISCO
switch(config)#vlan 20
switch(config)#vlan 31
switch(config)#int vlan 20
switch(if-config)#ip add 172.64.20.1 255.255.255.0
switch(if-config)#no shut
switch(if-config)#int vlan 31
switch(if-config)#ip add 192.162.31.1 255.255.255.0
switch(if-config)#no shut
switch(if-config)#exit
```

switch#ip routing

switch#copy run start

vtp client configuration:

```
switch#conf t
switch(config)#vtp mode client
switch(config)#vtp domain CISCO
switch#copy run start
```

14. In the use of 802.1X access control, which three protocols are allowed through the switch port before authentication takes place? (Choose three.)

- A. STP
- B. CDP
- C. EAP MD5
- D. TACACS+
- E. EAP-over-LAN
- F. protocols not filtered by an ACL

Answer: ABE

4. Which three statements are true regarding the above diagram? (Choose three.)

- A. A trunk link will be formed.
- B. Only VLANs 1-1001 will travel across the trunk link.
- C. The native VLAN for Switch B is vlan 1.
- D. DTP is not running on Switch A.
- E. DTP packets are sent from Switch B.

Answer: ACE

5. Which two statements are true about a switched virtual interface (SVI)? (Choose two.)

- A. An SVI is created by entering the no switchport command in interface configuration mode.
- B. An SVI is created for the default VLAN (VLAN1) to permit remote switch administration by default.
- C. An SVI provides a default gateway for a VLAN.
- D. Multiple SVIs can be associated with a VLAN.
- E. SVI is another name for a routed port.

Answer: BC

6. In the use of 802.1X access control, which three protocols are allowed through the switch port before authentication takes place? (Choose three.)

- A. STP
- B. CDP
- C. EAP MD5
- D. TACACS+
- E. EAP-over-LAN
- F. protocols not filtered by an ACL

Answer: ABE

7. What are three disadvantages of a router-on-a-stick configuration for InterVLAN routing? (Choose three.)

- A. InterVLAN routing cannot be filtered by the router.
- B. The router becomes a single point of failure for the network.
- C. Routers will not route STP BPDUs.
- D. There is a possibility of inadequate bandwidth for each VLAN.
- E. Additional overhead on the router can occur.
- F. NetFlow Switching is required for InterVLAN accounting.

Answer: BDE

8. Which two statements about the various implementations of STP are true? (Choose two.)

- A. Common Spanning Tree maintains a separate spanning-tree instance for each VLAN configured in the network.
- B. The Spanning Tree Protocol (STP) is an evolution of the IEEE 802.1w standard.
- C. Per-VLAN Spanning Tree (PVST) supports 802.1Q trunking.
- D. Per-VLAN Spanning Tree Plus(PVST+) is an enhancement to 802.1Q specification and is supported only on Cisco devices.
- E. Rapid Spanning Tree Protocol (RSTP) includes features equivalent to Cisco PortFast, UplinkFast, and BackboneFast for faster network reconvergence.
- F. Multiple Spanning Tree (MST) assumes one spanning-tree instance for the entire Layer 2 network, regardless of the multiple number of VLANs.

Answer: DE

9. What action should a network administrator take to enable VTP pruning on an entire management domain?

- A. enable VTP pruning on any client switch in the domain
- B. enable VTP pruning on every switch in the domain
- C. enable VTP pruning on any switch in the management domain
- D. enable VTP pruning on a VTP server in the management domain

Answer: D

10. Which technology manages multicast traffic at Layer 2 by configuring Layer 2 LAN interfaces dynamically to forward multicast traffic only to those interfaces that want to receive it?

- A. IGMP
- B. IGMP snooping
- C. PIM-DM
- D. DVMRP
- E. MOSPF

Answer: B

11. Examine the router output above. Which two items are correct? (Choose two.)

- A. Router A will assume the active state if its priority is the highest.
- B. If Ethernet 0/2 goes down, the standby router will take over.
- C. When Ethernet 0/3 of RouterA comes back up, the priority will become 105.
- D. The local IP address of Router A is 10.1.0.6.
- E. The local IP address of Router A is 10.1.0.20.

Answer: AC

12. Which statement is correct about 802.1Q trunking?

- A. Both switches must be in the same VTP domain.
- B. The encapsulation type on both ends of the trunk does not have to match.
- C. The native VLAN on both ends of the trunk must be VLAN 1.
- D. 802.1Q trunking can only be configured on a Layer 2 port.
- E. In 802.1Q trunking, all VLAN packets are tagged on the trunk link, except the native VLAN.

Answer: E

13. Which three interface commands will configure the switch port to support a connected Cisco phone and to trust the CoS values received on the port if CDP discovers that a Cisco phone is attached? (Choose three.)

- A. mls qos trust override cos
- B. mls qos trust cos
- C. mls qos trust device cisco-phone
- D. switchport priority extend cos\_value
- E. switchport voice vlan vlan-id

Answer: BCE

14. Refer to the exhibit.

On the basis of the information provided in the exhibit, which two sets of procedures are best practices for Layer 2 and 3 failover alignment? (Choose two.)

- A. Configure the D-SW1 switch as the active HSRP router and the STP root for all VLANs. Configure the D-SW2 switch as the standby HSRP router and backup STP root for all VLANs.
- B. Configure the D-SW2 switch as the active HSRP router and the STP root for all VLANs. Configure the D-SW1 switch as the standby HSRP router and backup STP root for all VLANs.
- C. Configure the D-SW1 switch as the active HSRP router and the STP root for VLANs 11 and 110. Configure the D-SW2 switch as the active HSRP router and the STP root for VLANs 12 and 120.
- D. Configure the D-SW1 switch as the standby HSRP router and the backup STP root for VLANs 12 and 120. Configure the D-SW2 switch as the standby HSRP router and the backup STP root for VLANs 11 and 110.
- E. Configure the D-SW1 switch as the standby HSRP router and the STP root for VLANs 11 and 110. Configure the D-SW2 switch as the standby HSRP router and the STP root for VLANs 12 and 120.
- F. Configure the D-SW1 switch as the active HSRP router and the backup STP root for VLANs 11 and 110. Configure the D-SW2 switch as the active HSRP router and the backup STP root for VLANs 12 and 120.

Answer: CD

15. If there are two equal cost paths to the root switch, what is the next criterion to determine the root port?

- A. lowest time to receive BPDUs
- B. lowest port ID
- C. lowest sender bridge ID
- D. highest MAC address on the receiving port

Answer: C

16. Which two multicast IP addresses can be represented by the multicast MAC address 0100.5e0A.0A07? (Choose two.)

- A. 228.10.10.7
- B. 228.10.10.8
- C. 228.10.138.7
- D. 229.11.10.7
- E. 229.138.10.7
- F. 229.138.10.8

Answer: AE

17. Refer to the above graphic. Switch A, the root bridge, is connected directly to Switch B over link L1 and to Switch C over link L2. The Layer 2 LAN interface on Switch C that is connected directly to Switch B is in the blocking state. Switch C detects a link failure on the currently active link L2 on the root port, which spanning tree enhancement will allow Switch C to unblock the blocked port and transition it to forwarding without going through the listening and

learning states?

- A. PortFast
- B. UplinkFast
- C. BackboneFast
- D. rapid spanning tree

Answer: B

18. Which spanning-tree feature will disable ports configured for PortFast in the event of a BPDU being received on those ports?

- A. BPDUGuard
- B. BPDU filtering
- C. UDLD
- D. Root Guard

Answer: A

19. A network is configured with VLANs 1 through 802.1 Q trunking is enabled between all switches. Currently, access ports for VLAN 3 exist only on Switch3 and Switch6. What must the administrator do to ensure that the other switches do not receive unnecessary broadcast packets for VLAN 3 while still allowing all other VLAN packets to cross?

- A. Configure VTP pruning.
- B. Configure Switch3 and Switch6 as transparent switches.
- C. Configure Switch1, Switch2, Switch4 and Switch5 as transparent switches.
- D. Nothing is required. Only Switch3 and Switch6 will receive VLAN3 packets by default.

Answer: A

20. Given the following configuration on a switch interface, what happens when a host with the MAC address of 0003.0003.0003 is directly connected to the switch port? switchport mode access switchport port-security switchport port-security maximum 2 switchport port-security mac-address 0002.0002.0002 switchport port-security violation shutdown

- A. The port will shut down.
- B. The host will be allowed to connect.
- C. The host will be refused access.
- D. The host can only connect through a hub/switch where 0002.0002.0002 is already connected.

Answer: B

[More 642-811 Information](#)

### **Related 642-811 Exams**

[642-825](#) *Implementing Secure Converged Wide Area Networks*

[642-892](#) *Composite Exam*

[642-812](#) *Building Cisco Multilayer Switched Networks*

[642-901](#) *Building Scalable Cisco Internetworks*

[642-845](#) *Optimizing Converged Cisco Networks*

[642-891](#) *Composite Exam*

[642-811](#) *Building Cisco Multilayer Switched Networks (BCMSN)*

[642-801](#) *Building Scalable Cisco Internetworks(BSCI)*

[642-821](#) *Building Cisco Remote Access Networks (BCRAN)*

[642-831](#) *Cisco Internetwork Troubleshooting (CIT)*

[642-813](#) *implementing cisco switched networks*

[642-902](#) *implementing cisco ip routing*

**Other Cisco Exams**

<u>646-363</u>	<u>646-563</u>	<u>642-357</u>	<u>350-018</u>	<u>642-091</u>	<u>642-052</u>	<u>642-845</u>	<u>640-861</u>
<u>646-229</u>	<u>642-511</u>	<u>646-011</u>	<u>642-067</u>	<u>640-816</u>	<u>642-812</u>	<u>650-059</u>	<u>646-590</u>
<u>646-046</u>	<u>640-460</u>	<u>642-144</u>	<u>642-975</u>				